


NOTES:
1. Material: N-BK7;
2. Design wavelength: 546 nm;
3. Focal length: F=+150 mm ± 2%;
4. Centration error: ≤ 3 arcmin;
5. G - Fine ground surface;
6. All dimensions are in mm;



Isometric view 1:1

Specifications are subject to change without notice
Dimensions are for reference only

| Parameters | | |
|---|---|---|
| | S1 | S2 |
| Shape | Convex | Plano |
| Radius of curvature | 77.8 | Infinity |
| Surface quality | 40-20 s/d | 40-20 s/d |
| Surface irregularity | λ/8 @632.8 nm | λ/8 @632.8 nm |
| Clear aperture | ≥90% | ≥90% |
| Protective chamfers | 0.2 - 0.3 mm x 45° | 0.2 - 0.3 mm x 45° |

Eksma Optics
info@eksmaoptics.com
www.eksmaoptics.com

N-BK7 pl/cx lens, D=38.1 mm, F=150 mm

The information in this drawing is property of EKSMA Optics. Any reproduction in part or as a whole without the written permission of EKSMA Optics is prohibited.

| Proprietary | | Name | Date | Part number | Rev. | Scale |
|---|---|---|---|---|---|---|
| | Approved | A.K. | 2019.02.01 | 110-0411E | A | 2:1 |
| | Drawn | M.B. | 2019.02.01 | | | |