


NOTES:
1. Material: N-BK7 (beamsplitter),
   Black anodized aluminium (housing);
2. G - Fine ground surface;
3. All dimensions are in mm;
4. Protective chamfers: 0.3 mm x 45°;
5. Beam deviation: <3 arcmin;
6. Laser damage threshold: >0.3 J/cm$^2$ at @1064nm, 10ns pulses;



Isometric view 1:2




A-A




Specifications are subject to change without notice
Dimensions are for reference only

| Parameters | | |
|---|---|---|
| | All sides | Hypotenuse |
| Shape | Plano | Plano |
| Surface flatness | λ/4 @633nm | λ/4 @633nm |
| Surface quality | 40-20 s/d | 40-20 s/d |
| Clear aperture | >90% | >90% |
| Coating | AR<0.25% @633nm | $R_s/T_p$>99.5/95% @633nm |

Eksma Optics
info@eksmaoptics.com
www.eksmaoptics.com

CP beamsplitter, H=L=T=15 mm

| Proprietary | | Name | Date | Part number | Rev. | Scale |
|---|---|---|---|---|---|---|
| The information in this drawing is property of EKSMA Optics. Any reproduction in part or as a whole without the written permission of EKSMA Optics is prohibited. | Approved | A.K. | 2021.04.27 | 430-0154-M2P | A | 2:1 |
| | Drawn | V.S. | 2021.04.27 | | | |